

## Model Y-4055

File Number: EX15799

### COMPANY

#### DUYAR VANA MAKINA SAN VE TIC A S

Osmangazi Mh. 2653 Sk. No:7  
Esenyurt, Istanbul 34522 Turkey

### MODEL INFO

Y-4055

GENERAL			
Pattern	Size, in.	End Configuration	Rated Pressure, psig (kPa)
NRS	2-1/2, 3, 4, 5, 6, 8, 10, 12	Flange & Flange	300 (2068)

### NOTES

#### Notes

Flanges comply with ASME/ANSI B16.1 Class 125, or ASME/ANSI B16.42 Class 150, or BS EN1092-2, or GB/T9113.1. Grooves comply with AWWA C606.

Mechanical Joints comply with ANSI/AWWA C110 and ANSI/AWWA C153. For 300 psi, use Face flange, for 200 psi, use Raised-face flange.



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."